Technical Data Sheet

Protecflam Industries
17/06/2026

Flamboard® ZZ

Protective screen complying with workplace safety requirements.

Description

This protective screen for welding, grinding, and all operations involving high-temperature projection risks complies with workplace safety requirements.Self-supporting and lightweight, the **Flamboard® ZZ** is easy to transport and adapts to all types of worksites. If necessary, it can be easily cut using a simple utility knife. The **Flamboard® ZZ** is fire-retardant on both sides.

Use

Lightweight and easy to handle, the **Flamboard® ZZ** is easily transportable and remains upright without any additional fixing.

Technical datas

Color: white
Height: 1 800 mm
Fold width: 820 mm
Thickness: 6 to 7 mm
Packaging: 80 folds per pallet (133 m^2 - +/- 100 kg)

Fire reaction classification

M1 according to test report No. CM-16-B-030 (conducted at FCBA).

Tests are carried out in a laboratory approved by the French Ministry of the Interior for fire reaction classification.

Storage

Store in a dry, enclosed area, protected from water and air, at temperatures between +5°C and +30°C. Keep in a cool, dry place..

Must be strictly protected against moisture!

protecflam

Protecflam Industries
31, rue de l'Etoile du Matin
FR- 44600 Saint Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80

Measured values

All technical values indicated in this technical data sheet are based on laboratory tests. External factors beyond our control may cause deviations in actual performance values.

Local regulations

The information provided in this technical data sheet applies to the corresponding product supplied by Protecflam Industries.

Safety notes

For further details, please refer to the current Safety Data Sheet available from Protecflam Industries.

protecflam

Protecflam Industries
31, rue de l'Etoile du Matin
FR- 44600 Saint Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80