Fiche Technique

Protecflam Industries
Edition 13/12/2017

Plastiflam® TACBAC / 65

Flame retardant adhesive floor protection

Description

Plastiflam® TACBAC / 65 is a temporary plastic protection in flame retardant, non-slip adhesive polyethylene, intended for the protection of flexible floors such as carpets or rugs.
Color: translucent white striped

Use

Temporary protection.
Can be used indoors and outdoors (waterproof).
Unroll the Plastiflam® TACBAC / 65, adhesive side against the floor to be protected, so as to cover the entire surface concerned. If necessary, cut with a cutter blade.
Leaves no glue residue after use.

Technical Data

thickness : 65 µm
dimensions : 100 cm x 100 ml (roll)

Fire Reaction

Plastiflam® TACBAC / 65 has been flame, smoke and toxicity tested to standards IMO (International Maritime Organisation) Resolution MSC 61/67 par Warrington Fire Research.

Fire classification IMO Flame Test Resolution A 653 Test Smoke & Toxicity - ISO Oxygen 4589-2

Storage

Storage in a room out of water out of air, at temperatures between +5 ° C and +23 ° C, for a maximum of 6 months after the date of manufacture. Store preferably in a cool and dry place. It is recommended not to expose the sheets to UV rays, high temperatures or high humidity.

protecflam

Protecflam Industries
rue de l'Etoile du Matin
FR- 44600 St Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80

Measured values

All the technical values indicated in this product technical sheet are based on laboratory tests. Circumstances beyond our control can lead to deviations from the actual values.

Safety remarks

For more detailed inofrmation, please consult the current safety data sheet from Protecflam Industries.

protecflam

Protecflam Industries
rue de l'Etoile du Matin
FR- 44600 St Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80