Technical Data Sheet

Protecflam Industries
Edition 15/06/2026

Veriflam® 3400 / 400

Fireproof fiberglass fabric

Description

Non-combustible fabric made of 100% fiberglass backing coated with a flame retardant polymer on both sides.

Technical data

Coating :	M0 thermosetting resin
Thickness (DIN ISO 4603/E :	0,40 mm
Colors :	Black / Blue / yellow
Width :	1550 mm
Length :	50 linear meters
Weight (DIN EN 12127) :	455 g/sq.m^2 ± 10%
Longitudinal resistance strength (DIN ISO 4606) :	3000 N/5 cm
Transversal resistance strength (DIN ISO 4606) :	2600 N/5 cm
Heat resistance :	min -36°C / max 600°C
Reaction to fire :	M0 - CSTB test report n° RA18-0188 Non-limited durability of the classification.

Storage

Store in a cool, dry place, at temperatures between + 5 ° C and + 23 ° C, for a maximum of 6 months after the date of manufacture.
It is recommended not to expose the fabric to UV rays, high temperatures or high humidity.

Values

All technical values stated in this product data sheet are based on laboratory tests. Circumstances beyond our control may lead to deviations from the actual values. For more details, contact Protecflam Industries.

protecflam

Protecflam Industries
31, rue de l'Etoile du Matin
FR- 44600 Saint Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80