Technical Data Sheet

Protecflam Industries
Edition 16/06/2026

Veriflam® AXT-W1

Black fire-resistant adhesive compatible with the Veriflam® XT-W1 HPV rain screen.

Description

Veriflam® AXT-W1 adhesive is compatible with **Veriflam® XT-W1**. It is a protective adhesive comprising silicone-coated paper, an adhesive compound and glass fabric.

Use

Veriflam® AXT-W1 offers high UV resistance. Easy to install and reinforced with fibreglass, it is highly tear-resistant. It must be used at temperatures above +5°C (lower temperatures have not been tested).

Fire Reaction

Euroclass **A2-s1,d0**

Technical Data

- **Width:** 75 mm
- **Length:** 25 m
- **Basis weight:** 340 g/m²
- **Thickness:** 0.34 mm
- **Packaging:** 16 rolls
- **Tensile strength:** Warp: 750 N/cm I Weft: 600 N/cm• Tensile strength:

- Longitudinal: 4,200 N/50 mm - EN 12311-1

- Transverse: 3,100 N/50 mm - EN 12311-1

- **Tear strength:**

- Longitudinal: 290 N - EN 12310-1
- Transverse: 390 N - EN 12310-1

- **Elongation**:

- Longitudinal: 6% - EN 12311-1
- Transverse: 5% - EN 12311-1

- **Peel strength:**

- After 72 hours: 20 N/50 mm - EN 12316-1

protecflam

Protecflam Industries
31, rue de l'Etoile du Matin
FR- 44600 Saint Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80

Storage

Store in a dry, well-ventilated area at temperatures between +5 °C and +23 °C.
Store preferably in a cool, dry place.

Measured values

All technical specifications given in this product data sheet are based on laboratory tests. Circumstances beyond our control may result in deviations from the actual values.

Safety notes

For further details, please contact Protecflam Industries.

protecflam

Protecflam Industries
31, rue de l'Etoile du Matin
FR- 44600 Saint Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80