Technical Data Sheet

Protecflam Industries
Edition 16/06/2026

Veriflam® FI 1120

Non-flammable coated silica fibre fabric

Description

Glass fabric made of a 100% silica fibre backing coated with vermiculite on both sides.

Technical Data

Coating: Vermiculite
Thickness (DIN ISO 5084): 1.40 mm
Colour: Toffee
Width: 920 mm
Length: 50 m
Mass per unit area (DIN EN 12127): 1120 g/m²
No. of warp threads (DIN EN 1049-2): 166 threads/10 cm
No. of weft threads (DIN EN 1049-2): 128 threads/10 cm
Temperature resistance: 1300°C max

Storage

Store in a dry, well-ventilated area at temperatures between +5 °C and +23 °C for a maximum of 6 months after the date of manufacture. Store preferably in a cool, dry place. It is recommended that the fabric is not exposed to UV light, high temperatures or high humidity.

Measured values

All technical specifications given in this product data sheet are based on laboratory tests. Circumstances beyond our control may result in deviations from the actual values.

Safety notes

For further details, please contact Protecflam Industries.

protecflam

Protecflam Industries
31, rue de l'Etoile du Matin
FR- 44600 Saint Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80