Technical Data Sheet

Protecflam Industries
Edition 15/06/2026

Veriflam® TG200 / 9L

Non-combustible glass fabric

Description

Non-combustible glass fabric with aluminum foil laminated on one side.
Appearance: white with aluminized side

Use

Protection of floors, walls, etc.
Making of covers or tarpaulins.
Packaging or decorative elements.
Washable with soapy water.

Technical Data

Thickness: 220 µm
Width: 100 cm
Surface weight: 250 g/m² ± 10%
Breaking strength (L / T): >2300 / >1400 N/5cm (EN ISO 4606)

Resists abrasion and bending
Reflection of thermal rays
Maximum radiation temperature: approx. 1000 ° C
Maximum contact temperature: 180 ° C

Fire Reaction

IMO

Storage

Store indoor, out of water out of air, at temperatures between +5 ° C and +23 ° C, for 6 months maximum after the date of manufacture. Store preferably in cool and dry conditions.
It is recommended not to expose the fabric to UV rays, high temperatures or high humidity.

protecflam

Protecflam Industries
31, rue de l'Etoile du Matin
FR- 44600 Saint Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80

Values

All technical values indicated in this product data sheet are based on laboratory tests. Circumstances beyond our control can lead to deviations from actual values.

Safety Remarks

For further information, please contact Protecflam Industries.

Protecflam Industries
31, rue de l'Etoile du Matin
FR- 44600 Saint Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80