Technical Data Sheet

Protecflam Industries
Edition 28/08/2026

Veriflam® 3200

Fire-resistant glass fabric

Description

Non-flammable glass fabric consisting of a 100% glass fibre backing coated on both sides with a flame-retardant polyurethane.

Use

Protection for floors, walls, etc.
Making covers or tarpaulins.
Packaging or decorative items.
Washable with soapy water.

Technical Data

Thickness: 400 µm (DIN ISO 4603 /E)
Width: 100 / 155 / 200 cm
Grammage: 455 g/m² ± 10% (DIN EN 12127)
Warp tensile strength: 650 N/cm (DIN ISO 4606)
Weft tensile strength: 580 N/cm (DIN ISO 4606)
Temperature resistance: -36°C min. / 200°C max.
Temperature resistance of the fiberglass base fabric: up to 600°C.
Colour: grey

Resistant to abrasion and creasing
Reflects thermal radiation

Fire Reaction

Veriflam® 3200 has been tested to Euroclass A2, s1-d0 for reaction to fire.

Storage

Store in a dry, well-ventilated area at temperatures between +5 °C and +23 °C for up to 6 months after the date of manufacture. Store preferably in a cool, dry place.

protecflam

Protecflam Industries
31, rue de l'Etoile du Matin
FR- 44600 Saint Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80

It is recommended that you do not expose the fabric to UV light, high temperatures or high humidity.

Measured values

All technical specifications given in this product data sheet are based on laboratory tests. Circumstances beyond our control may result in deviations from the actual values.

Safety notes

For further details, please contact Protecflam Industries.

protecflam

Protecflam Industries
31, rue de l'Etoile du Matin
FR- 44600 Saint Nazaire
www.protecflam.fr
contact@protecflam.com
+33(0)2 40 90 10 80